



GENERAL NOTES:

1. COMPONENTS TO MEET ASTM C478, STANDARD SPECIFICATION FOR REINFORCED CONCRETE MANHOLE SECTIONS.
2. CONCRETE: $f'_c=3000$ PSI @28 DAYS.

DRAWING DEVELOPED FOR ML-3/ML-4 PROJECTS. FOR ML-1/ML-2, ADDITIONAL REQUIREMENTS AND QA REVIEWS ARE REQUIRED. (REMOVE THIS NOTE WHEN INSERTED INTO A DRAWING PACKAGE).

NO	DATE	CLASS	REV	ADD	DESCRIPTION	OWN	DSGN	CHKD	SUB	APP
1	8-23-02	U			GENERAL REVISION AND DWG. NO. WAS ST5721.	RP	EH	MS	EH	TO

ENGINEERING STANDARDS PROGRAM

ENGINEERING STANDARDS MANUAL		DESIGN	R.PEARSON
		CHECKED	M.SMITHOUR
CONCRETE CATCH BASIN DETAIL STORM WATER		DATE	0-28-99
BLDG X	TA-X	APPROVED FOR RELEASE	
SUBMITTED	DISCIPLINE POC: E. HOTH	STANDARDS MANAGER: TOBIN ORUCH	
Los Alamos NATIONAL LABORATORY		PO Box 1583 Los Alamos, New Mexico 87545	1 OF 2
CLASSIFICATION: U	REVIEWER: LARRY BAYS	DATE:	
PROJECT ID	DRAWING NO	REV	
CHAPTER 3		ST-G3030-1	1

© 2002, Engineering Standards Program, LBNL-544-00000-00000000, 08/03/02 @ 1:31, 020808